




RLC16

Relay card

FEATURES

- » From the Vibro-Meter® product line
- » Relay card with screw terminal strip
- » 16 relays with change-over contacts
- » Relay driver inverter logic (jumper selectable)
- » Low contact resistance
- » Low capacitance
- » High through power
- » Live insertion and removal of cards (hot-swappable)
- » Conforms to EC standards for EMC



RLC16

DESCRIPTION

The RLC16 relay card is designed for use in the VM600 series of machinery protection systems and condition and performance monitoring systems, from Meggitt Sensing Systems' Vibro-Meter® product line. It is an optional card, for use when the four relays on the IOC4T input/output card are insufficient for the application and additional relays are required.

The RLC16 is installed in the rear of the VM600 (ABE04x) rack and connects directly to the rack backplane via a single connector.

The RLC16 contains 16 relays with change-over contacts. Each relay is associated with 3 terminals on a screw terminal strip accessible at the rear of the VM600 rack.

The relays are controlled by open-collector drivers under software control. Jumpers on the RLC16 card allow the selection of relay normally energized (NE) or normally de-energized (NDE).




Information contained in this document may be subject to Export Control Regulations of the European Union, USA or other countries. Each recipient of this document is responsible for ensuring that transfer or use of any information contained in this document complies with all relevant Export Control Regulations. ECN N/A.

SPECIFICATIONS

Relay characteristics

Relay names	: RL1 to RL16
Type	: PE014005
Contact arrangement	: 1x COM, 1x NC and 1x NO contact/relay. All relay contacts are available on J1, J2 and J3.
Nominal rated voltage	: 250 V _{AC}
Nominal rated current	: 5 A _{AC}
Maximum breaking capacity (without contact protection)	: 1250 VA
Maximum DC load breaking capacity curve:	



Operate / release / bounce time	: Typically 8 / 8 / 6 ms
Dielectric strength test voltages	
• Between open contacts	: 1000 V _{AC}
• Between contact and coil	: 4000 V _{AC}
Mechanical life	: 15 x 10 ⁶ operations
Electrical life	: >10 ⁵ operations

⚠ When used in a VM600 Slimline rack (ABE056) with a DC power supply, the relay contacts on a RLC16 card have a maximum switching voltage of 70 V_{DC} / 33 V_{AC} (RMS) (46.7 V_{AC} (PEAK)).

Relay card characteristics

Presentation	: 16 relay PCB
Relay state	: Normally energized or normally de-energized (jumper selectable)
External connections	: Screw terminal connectors (J1, J2 and J3)
Mounting	: Installs in the rear of a VM600 rack and connects to the rack's backplane via a connector
Temperature range	: See above relay characteristics
Humidity	: ≤95% (RH non-condensing)

Power supply to RLC16

Supply voltage	: +5 V _{DC}
Consumption	: 40 mA x16 (per relay)

SPECIFICATIONS *(continued)*

Environmental

Operating

- *Temperature* : -25 to +65°C (-13 to +149°F)
- *Humidity* : 0 to 90% non-condensing

Storage

- *Temperature* : -40 to +85°C (-40 to +185°F)
- *Humidity* : 0 to 95% non-condensing

Vibrations and shock

: See general VM600 rack specifications

Physical

Height	: 6U (262 mm, 10.3 in)
Width	: 20 mm (0.8 in)
Depth	: 125 mm (4.9 in)
Weight	: 0.30 kg (0.66 lb)

ORDERING INFORMATION

To order please specify

Type	Designation	Ordering number
RLC16	Relay card	
	'Standard' version	200-570-000-1Hh
	'Separate circuits' version, in accordance with IEC/CEI 60255-5	200-570-000-2Hh

Notes

"Hh" represents the hardware version.

"H" increments are for major modifications that can affect product interchangeability.

"h" increments are for minor modifications that have no effect on interchangeability.

Headquartered in the UK, Meggitt PLC is a global engineering group specializing in extreme environment components and smart sub-systems for aerospace, defence and energy markets. Meggitt Sensing Systems is the operating division of Meggitt specializing in sensing and monitoring systems, which has operated through its antecedents since 1927 under the names of ECET, Endeeco, Ferroperm Piezoceramics, Lodge Ignition, Sensorex, Vibro-Meter and Wilcoxon Research. Today, these operations are integrated under one strategic business unit called Meggitt Sensing Systems, headquartered in Switzerland and providing complete systems, using these renowned brands, from a single supply base. The Meggitt Sensing Systems facility in Fribourg, Switzerland was formerly known as Vibro-Meter SA, but is now Meggitt SA. This site produces a wide range of vibration and dynamic pressure sensors capable of operation in extreme environments, leading-edge microwave sensors, electronics monitoring systems and innovative software for aerospace and land-based turbo-machinery.



All statements, technical information, drawings, performance rates and descriptions in this document, whilst stated in good faith, are issued for the sole purpose of giving an approximate indication of the products described in them, and are not binding on Meggitt SA unless expressly agreed in writing. Before acquiring this product, you must evaluate it and determine if it is suitable for your intended application. Unless otherwise expressly agreed in writing with Meggitt SA, you assume all risks and liability associated with its use. Any recommendations and advice given without charge, whilst given in good faith, are not binding on Meggitt SA.

Meggitt Sensing Systems takes no responsibility for any statements related to the product which are not contained in a current Meggitt Sensing Systems publication, nor for any statements contained in extracts, summaries, translations or any other documents not authored by Meggitt Sensing Systems. We reserve the right to alter any part of this publication without prior notice.

In this publication, a dot (.) is used as the decimal separator and thousands are separated by thin spaces. Example: 12345.67890.

Sales offices

Meggitt Sensing Systems has offices in more than 30 countries. For a complete list, please visit our website.



Your local agent

Head office

Meggitt SA
Route de Moncor 4
PO Box 1616
CH - 1701 Fribourg
Switzerland

Tel: +41 (0)26 407 11 11
Fax: +41 (0)26 407 13 01

www.meggittsensingsystems.com
www.vibro-meter.com